

Part No.	Description
900M	iManifold™ Wireless Digital Refrigeration Manifold. Includes strap with hook, (2) 901M pipe strap probes, (6) AA batteries and Quick Start Guide.
900C	iConnect™ Portable Measurement System. Use wireless & wired probes to simultaneously measure & monitor temperatures, pressures, or relative humidity. Includes (6) AA batteries. Accessories by Cooper-Atkins® Specifically for iManifold™
901M	Thermistor Pipe Strap Surface Probe. Temp range: -25° to 212°F. Patented. 8" elastic strap.
902M	Thermistor Air Probe (0.5") with 4" cord. Temp range: -40° to 200°F.
903M	Thermistor Air Probe (0.5") with 12 ft. cord. Temp range: -40° to 200°F.
904M	General Purpose Thermistor Puncture Probe (3.5"). Used to measure temperatures by insertion or immersion. Temp range: -40° to 300°F. 6 ft. cable (uncoiled).
905M	Thermistor Pipe Clamp Surface Probe. For pipe diameters up to 1-3/8" (3.5cm).
908M	Thermistor Extension Cable, 10 ft.
909M	Thermistor Extension Cable, 50 ft. Wireless Probes [all wireless probes also act as repeaters]
911M	Relative Humidity and Temperature. Measures return & supply wet-bulb, dry-bulb, relative humidity.
912M	Temperature. Has 2 side ports to plug in any optional wired probes.
913M	Low Pressure & Temperature. Use for measuring low side system pressure & line temperatures with optional wired probes.
914M	High Pressure & Temperature. Use for measuring high side system pressure & line temperatures with optional wired probes. iManifold Performance Test Kits
915M	iManifold Performance Test Kit. 900M, 911M (2), 902M, 905M, TB52 Tool Bag
916M	iManifold Performance Test Kit with Hoses. 900M, 911M (2), 902M, 905M, 955MRS (5 ft.) hose set w/low loss ball valve shut-off, TB52 Tool Bag
920M	iManifold Performance Test Kit with Repeater Probe. 900M, 911M (2), 912M, 902M, 905M, 955MRS (5 ft.) hose set w/low loss ball valve shut-off, TB52 Tool Bag iConnect Performance Test Kits
915C	iConnect Airside Performance Test Kit. 900C, 911M (2), TB52 Tool Bag
916C	iConnect Performance Test Kit with Airflow Measurement. 900C, 901M (2), 902M, 905M, 911M (2), 912M, 913M, 914M, TB52 Tool Bag

**Part
No. Description****CoolSaver Performance Test Kits**

- 917M iManifold A/C Heat Pump Performance Test Kit.** 900M, 911M (2), 912M, 903M, 955MRS (5 ft.) hose set w/low loss ball valve shut-off, TB52 Tool Bag
- 918M iManifold Custom Refrigeration Multi Compressor/4 Circuits Performance Test Kit.** 900M, 911M (2), 912M, 913M (3), 914M (3), 901M, 903M, 955MRS (5 ft.) hose set w/low loss ball valve shut-off, TB52 Tool Bag
- 917C iConnect Residential Test Kit with Airflow Measurement.** 900C, 911M (2), 912M, 913M, 914M, 901M (2), 903M, TB52 Tool Bag
- 918C iConnect Custom Refrigeration Multi Compressor/4 Circuits Performance Test Kit.** 900C, 911M (2), 912M, 913M (4), 914M (4), 901M (8), 903M, TB52 Tool Bag
- NYSERDA Approved Quality Maintenance Kit**
- 919M iManifold Commercial Quality Maintenance (QM) Kit for NYSERDA Program.** 900M, 900C, 911M (2), 912M, 913M, 914M, 901M (2), 902M, 905M, TB52 Tool Bag